



PHONE 864.472.4596
FAX 864.473.1125
FAX 864.472.3866

P.O. Box 769
95 Laurel Lane
Campobello, SC 29322

Landrum Farmers Market Pavilion
Landrum, South Carolina
Douglas R. Hurlbert, Arch.

Addendum 1, Pg A Ref. Dwg. E-1, Rev. 0, 11-11-20
SCALE: None
DATE: 12-15-20

LIGHT FIXTURE SCHEDULE

MARK	FIXTURE DATA					ELECTRICAL DATA		LAMP DATA				DRIVER / BALLAST		OPTIONS (NOTE 1)					DESIGN BASED ON		REMARKS		
	TYPE	DIMENSIONS	MOUNTING	SERVICE	DIRECTION	VOLTAGE	WATTAGE	TYPE	QTY	LUMENS	COLOR	CRI	TYPE	QTY	LENS	DISTRIBUTION	BATTERY*	DIMMER / CONTROLS	MOUNTING HARDWARE	MOUNTING HEIGHT		MANUFACTURER	SERIES
CA	CAN	11" DIA	SURFACE	OUTDOOR WET	DIRECTIONAL	MVOLT	15.2	LED	-	1352	3500K	90	LED	1	FROSTED	STANDARD	-	TIMER	SURFACE	VARIES	JUNO	JSF 111N	1
CG	CAN	13" DIA	SURFACE	INDOOR / WET	DOWN	MVOLT	20.2	LED	-	1843	3500K	90	LED	1	FROSTED	STANDARD	-	0-10V	SURFACE	10'-0"	JUNO	JSF 131N	1
EB	EMERGENCY	-	CEILING / WALL	INDOOR	DIRECT / DOWN	120/277	6.6	LED	-	640	-	-	-	1	-	STANDARD	INTEGRAL	-	-	7'-6"	LITHONIA	ELM2LED	-
EC	EMERGENCY	-	CEILING / WALL	INDOOR	-	120/277	3.0	LED	-	-	-	-	-	1	-	STANDARD	INTEGRAL	-	-	7'-6"	LITHONIA	ECB LED M6	-
ED	EMERGENCY	-	WALL	OUTDOOR / WET	-	120/277	3.0	LED	-	-	-	-	-	1	-	STANDARD	INTEGRAL	-	-	7'-6"	LITHONIA	AFB	-
EE	EMERGENCY	-	WALL	INDOOR	-	120/277	30.0	LED	-	-	-	-	-	1	-	STANDARD	INTEGRAL	-	SURFACE ENCLOSED	STRUCTURE	MULE	EHE B8 30 S	-
KJ	TRACK	4"	STRUCTURE	INDOOR	-	-	-	-	-	-	-	-	-	-	-	-	-	-	SURFACE	17'-6"	JUNO	IT 4	1
KZ	TRACK	4"x7"	TRACK	INDOOR	DOWN	120	23.0	LED	-	1500	3500K	85	LED	-	-	SPOT	-	ELV	TRACK	17'-6"	WAC	JWTK LED23	1
PB	PENDANT	19" X 5"	PENDANT	INDOOR	DOWN	MVOLT	82.1	LED	-	10417	3500K	70	LED	1	FROSTED	TSM	-	-	PENDANT	17'-6"	LITHONIA	VCPGX LED	1
SA	SURFACE	24"	SURFACE	INDOOR/WET	DOWN	MVOLT	19.1	LED	-	2981	3500K	80	LED	1	CLEAR	STANDARD	-	-	BRACKETS	10'-0"	LITHONIA	FEM LED	1
VB	WALL	2"	WALL	INDOOR/DAMP	DIRECTIONAL	MVOLT	17.7	LED	-	1302	3000K	90	LED	1	FROSTED	STANDARD	-	-	WALL MOUNT	7'-6"	LITHONIA	FMVTRL	1
WE	WALL	16"x12"	WALL	OUTDOOR / WET	DOWN	120/277	18.0	LED	-	1830	3500K	80	LED	1	-	STANDARD	-	TIMER	WALL MOUNT	TBD	SPECTRUM	AR1214GV	1
WE2	WALL	3/4"x46"	SURFACE	OUTDOOR / WET	DOWN	24V	2.8 W/FT	LED	-	165 LM/FT	3000K	95	LED LV	1	MILKY WHITE	240 DEG	-	TIMER	ALUM CHANNEL	TBD	DURA LAMP	DFNTB283024	1,2

NOTE 1: ALL DIMMING CONTROLS TO BE 0-10v DC WHERE POSSIBLE. EC TO COORDINATE FIXTURE DIMMING REQUIREMENTS WITH SUPPLIERS.
NOTE 2: FIXTURE OPTIONS FOR LENGTH, ENDS, MOUNTING CHANNEL, AND COLORS TO BE COORDINATED WITH ARCHITECT PRIOR TO ORDERING.
NOTE *: ALL LIGHTING SUBMITTALS AND PROPOSED BUDGETS SHOULD INCLUDE AMPLE ALLOWANCES FOR ALL TRIM, COLOR, MOUNTING, LAMP, LUMEN OR LENS OPTIONS TO BE CHOSEN BY OWNER/ARCHITECT
NOTE **: REFER TO GENERAL NOTE "HH" FOR APPLICABILITY TO LISTED MODEL NUMBERS.
NOTE ***: LIGHTING SUBSTITUTIONS ARE TO BE APPROVED BY ARCHITECT/ENGINEER BEFORE PURCHASE.
NOTE ****: ALL FINAL LOCATIONS, PLACEMENTS AND POSITIONS TO BE COORDINATED WITH OWNER/ARCHITECT